



### SPECIFICATIONS

<b>Dimensions</b>	Adjustable in height from 30 to 39 inches
<b>Weight</b>	3 lbs (without voltmeter and half cell)
<b>Material</b>	Aluminum tubing
<b>Reel</b>	Pflueger Model 1595 ½ RC Single Action Reel
<b>Wire</b>	100 (minimum) feet of #22 awg 7/30 tinned copper with 0.015 inch (minimum) avg thick PVC coated wire (red).
<b>Voltmeter/Data Collector Mount</b>	Universal mounting with industrial grade Velcro®
<b>Electrode/Half Cell</b>	¼ - 20 Female threaded connector compatible with any half cell
<b>Set-up</b>	Fully wired to accept any voltmeter/data collector
<b>Tools</b>	One (1) 7/16 inch nut driver mounted on cane.
<b>Contact Information</b>	<p><b>For More Information:</b>          Jason Rine          P. O. Drawer 190          Clarksburg, WV 26302-0190          Toll free 877.624.9700          Fax 304.622.0981          E-mail <a href="mailto:j.rine@mSESinc.com">j.rine@mSESinc.com</a>  <a href="http://www.mSESproducts.com">www.mSESproducts.com</a></p>



### FEATURES

- Fully wired ready for use
- Compatible with any voltmeter and data collector
- Compatible with any half cell/electrode
- Ergonomic design

Voltmeter and Half Cell not supplied with Test Cane