



**SPECIFICATIONS**

<b>Dimensions</b>	Adjustable in height from 30 to 39 inches
<b>Weight</b>	6 lbs (without data collector and half cell)
<b>Material</b>	Aluminum tubing
<b>Reel</b>	Pen 324 GTi Level Wind Reel with Reel mounted on cane.
<b>Wire</b>	250 feet (minimum) of #22 awg 7/30 tinned copper with 0.015 inch (minimum) avg thick PVC coated wire (red).
<b>Data Collector Mount</b>	Data collector mounting bracket with adjustable screw grips.
<b>Data Entry</b>	Data Cane wired with a data entry button that allows for direct input to the data collector.
<b>Electrode/Half Cell</b>	¼ - 20 female threaded connector compatible with any half cell.
<b>Set-up</b>	Fully wired to accept most data collectors with direct data entry button.
<b>Tools</b>	One (1) 7/16 inch nut driver mounted on cane.
<b>Contact Information</b>	<p><b>For More Information:</b>          Jason Rine          P. O. Drawer 190          Clarksburg, WV 26302-0190          Toll free 877.624.9700          Fax 304.622.0981          E-mail <a href="mailto:j.rine@mSESinc.com">j.rine@mSESinc.com</a>  <a href="http://www.mSESproducts.com">www.mSESproducts.com</a></p>



**FEATURES**

- Fully wired ready for use
- Direct data entry button
- Compatible with most data collectors
- Compatible with any half cell/electrode
- Ergonomic design

Data Collector and Half Cell not supplied with Data Cane

**SKU 725**